

TremGlaze LEF

Table of Contents

TremGlaze LEF Data Sheet - EN

1

Tremco Polyurethane Foam Cleaner Data Sheet -
EN

2

Product Description

TremGlaze® LEF is a versatile, one-component, polyurethane foam in an aerosol can designed for window and door and retro-fit installations. This low pressure product reduces air infiltration and prevents heat loss in a variety of applications.

Basic Uses

Apply TremGlaze LEF onto any clean surface to fill, insulate and seal around windows, door frame joints, beneath base plates, mud sills, T-joints, top plate penetrations, corner joists, exterior cracks, around utility panels, pipes, duct penetrations and much more. It is specifically designed to be dispensed as a bead for filling cracks, crevices and to fill smaller cavities on flat or irregular surfaces. Recommended application temperature is from 14 to 94 °F (-10 to 35 °C).

Features and Benefits

- Single-component polyurethane foam with a (H)CFC-free propellant.
- Low Pressure Build.
- High yield versus existing polyurethane foams.
- Low water absorption.
- Quick tack-free time.
- Excellent properties at low ambient temperatures.

Availability

TremGlaze LEF is available for purchase from your authorized Tremco distributor. Light Green

Storage

Store in a cool, dry area.

Do not expose to open flame or store above 120 °F (49 °C).

Always store the gun with the foam or the polyurethane foam cleaner attached to the can.

Always store cans in upright position to avoid valve obstruction.

Do not install TremGlaze LEF Foam when ambient or surface temperatures are below 14 °F (-10 °C).

Limitations

- Use only in well-ventilated areas.
- Protect from direct exposure to UV and driving rain.
- TremGlaze LEF can be used in conjunction with other T3 products create an effective, three-level seal.

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or refund the purchase price of the quantity of Tremco Products proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Color		Light Green
Density	ASTM D3574	0.94 to 1.56 lb/ft ³
Thermal Conductivity	ASTM C518	3.8 to 4.5 hr - °F - ft ² /BTU
Compression Set	ASTM D3574	8.7 psi @ 10% deformation
Fire Testing	ASTM E84	Flame Spread: 10
Smoke Development		15
Service Temperature Range		-40 to 190 °F (-40 to 90 °C)
Tack Free Time	FEICA 1014	10 minutes (73 °F, 50% RH)
Cutting Time	FEICA 1005	45 minutes (73 °F, 50% RH)
Full Cure		24 hr (73 °F, 50% RH)
Thermal Conductivity	ASTM C518	3.8 to 4.5 hr - °F - ft ² /BTU

0316/TGLEFDS-GL

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555



Product Description

Tremco® Polyurethane Foam Cleaner is a multi-purpose cleaning agent used to dissolve uncured or fresh polyurethane foam, formulated without the use of any ozone-depleting materials. The product is uniquely designed for cleaning of the one-component professional dispensing units, and for general cleaning purposes such as tools, work surfaces, etc.

Basic Uses

Tremco Polyurethane Foam Cleaner can be used to clean the one-component dispensing unit to keep internal and external parts working effectively. It may also be used for dissolving uncured one-component polyurethane foam in most applications.

Features and Benefits

- Pre-pressurized in an aerosol spray can
- Can be fitted directly to a PU foam gun, or used as a handheld aerosol can
- Dispenses in the upright or inverted position
- Evaporates quickly

Availability

Tremco PU Foam Cleaner is immediately available from your local Tremco Field Representative, Distributor or Warehouse.

Packaging

16 oz. (500 ml) can - 12/case

Colors

Clear

Shelf Life

12 months when stored as recommended in original unopened containers.

Storage

Store in cool, dry area. Do not expose to open flame or temperatures above 100°F (38°C) to avoid excessive pressure build up. TremGlaze Polyurethane Cleaner is reusable by following product instructions.

Special Handling: WARNING:

Contents are extremely flammable. Never use near open flame, sparks, heat sources or other potential sources of ignition. Vapors may cause flash fire if ignited. Contents are under pressure. Do not puncture or incinerate even when empty. Do not place in hot water or near radiators, stoves or other sources of heat or store above 100°F (38°C). Do not freeze.

Limitations

- Cured foam cannot be dissolved with Tremco Polyurethane Foam Cleaner
- Use only in well-ventilated areas.

Preparation

Shake can well before using. For general cleaning purposes, insert the red spray activator onto the valve stem of the can. With arrow pointing towards the surface to be cleaned, slowly depress the red activator to spray cleaning agent. In case of delicate surfaces or fabrics, test a concealed area for evaluation. Wipe off excess residue or rub fabrics if necessary.

Recommended temperature for use is 75°F (24°C).

Application

Dispensing unit cleaning: Follow general cleaning instructions after the application of polyurethane foam has been completed to remove any fresh foam internally from the dispensing unit adapter and barrel opening. For a multiple foam can project it is not necessary to flush the dispensing unit after every can; if switching to a new can of foam, always replace the empty product container immediately.

While holding red spray activator aside, screw Tremco Polyurethane Foam Cleaner container onto dispensing unit adapter until it will go no further. Do not over tighten.

Carefully pull the trigger until solvent extrudes from the gun tip. Release the trigger and let cleaning agent soak in for one to two minutes. Pull trigger and dispense cleaning agent into suitable container. If necessary, repeat procedure two to three times until only clear cleaning agent appears from barrel.

Do not use pointed or sharp objects for cleaning of dispensing units. Wear impervious gloves, eye protection, and protective clothing when using. Read all instructions and safety information (SDS) prior to use of any product. **KEEP OUT OF REACH OF CHILDREN.**

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase price of the quantity of Tremco Products proven to be defective and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

0916/TPFOAM CLEANERDS-ST

Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555